



**EDWARD  
BULMER**  
NATURAL PAINT

# Water Based Gloss Woodwork and Metalwork

**Water Based Gloss** is an eggshell paint with a gloss finish which is suitable for use on both interior and exterior woodwork and metalwork, including radiators. This environmentally friendly, water based, eggshell paint is solvent free, non-yellowing and water-thinnable. It is a quick drying paint made with plant oils, minerals and natural pigments and bound with a novel semi-natural binder (Decovery®). Consistently ecological choice of raw materials, all ingredients are declared. **Water Based Gloss** has a durable, gloss finish which will enhance and protect your surfaces.

## Pack Size

1 litre and 2.5 litres.

## Colour range

Available in all 102 colours, as well as our shades in the Edward Bulmer Natural Paint ranges.

## Characteristics

Innovative, hard-wearing, water repellent paint, with gloss finish (80% sheen) for use on interior and exterior woodwork and metalwork. It is not a high gloss finish. It is suitable for radiators up to 70 degrees C. **To be stirred thoroughly using the wooden stirrer before use.** Water Based Gloss is not suitable for floors.

The product ensures excellent indoor air quality and the lowest VOC rated eggshell paint available at <1g/L. Breathable with Sd value of <0.3.

## Surface Preparation - Wood

The surface must be dry, clean, solid and coatable. Thoroughly sand existing coatings and clean off all dust. Existing coatings that are non-recoatable or unstable should be completely removed by sanding or stripping. Suitable wood fillers should be applied before application of any paint products.

## Priming

**PLEASE DO NOT PRIME WITH ACRYLIC PRIMERS.**

**Natural paints do not always adhere to PVC primers so avoid if possible, this warning includes the use of Zinsser which contains hazardous chemicals. If the surface has already been primed it is important to ascertain what primer has been used and then advice can be given about suitability of top coat.**

All bare wood should be primed with **Edward Bulmer Water Based Primer** to create a uniform, coatable surface. All MDF and PLY MUST be primed with **Edward Bulmer Water Based Primer** or the paint will be absorbed.

Bleeding knots on bare woods should be pre treated with **Water Based Primer**. Apply 2 coats of primer over knots to prevent bleeding.

Previously painted wood should be sanded thoroughly and cleaned off before applying at least 2 top coats.

## Surface Preparation - Metal

For iron parts that are not factory primed, clean and sand thoroughly to remove corrosion. Prime with a **Edward Bulmer Rust-Protection Primer**. Allow to dry thoroughly. For ferrous metals pre-primed by the manufacturer and not exhibiting any corrosion, clean and sand thoroughly and apply a first coat diluted with 5%

water.

Not appropriate for galvanized steel or nonferrous metals.

## Application – All surfaces

**Stir well before use** and check correct colour before application. All surfaces should be clean and dry. The ambient temperature should be above 10°C and below 30°C at 50-60% rh. Thoroughly stir and apply 2/3 coats evenly (and then lay off in the direction of the grain – for wood), using brush or foam/short pile roller. Sand lightly to make sure surface is dry before recoating and remove dust between coats. Also suitable for spraying: High pressure, mist reduced, airmix. Tested with Wagner SF23Plus and pistol Vector Grip. Nozzle type FineFinish TT3, nozzle size 410 gun filter red. Spray pressure 100 bar.

## Eco Paint Tools

We recommend using eco brushes, trays, rollers and other tools made in the UK by Eco Union, which are available on our website [www.edwardbulmerpaint.co.uk](http://www.edwardbulmerpaint.co.uk).

## External Painting

Do not expose unfinished coats to wet weather for over 48 hours. Check each coat is dry by sanding lightly before applying next coat. Do not paint when day or night time temperature is less than 10 degrees C or in driving rain or snow. Check annually and repair any defects immediately. Clear standing water on flat surfaces.

## Drying (23 °C/ 50% rel. humidity)

Dust dry after approximately 2 hours, re-coatable after approximately 6 hours. Fully cured after approximately 24 hours.

## Physical/Technical Characteristics

Working conditions: Min 10°C, max 30°C. Max. RH 85%; optimal is 20-23°C at 50-65 RH  
Density: 1.02 – 1.30 g/cm<sup>3</sup> depending on colour shade  
Gloss level: 5 at 20°, 80 at 60°, 95 at 85° measured in white  
VOC content: ≤1 g/L (Cat A/dwb, max permissible 130g.L) which is 0.09%.  
Perspiration and saliva-fast (DIN 53160 / EN 71 Part 3)  
Safe for toys (DIN EN71 part 3)  
Abrasion resistance: Class 1 (EN 13300).  
Opacity/covering: Class 1 @ consumption of 0.08l/m<sup>2</sup> (12.5m<sup>2</sup>/L) (EN13300)  
Breathability: Sd value<0/3 (in testing)

## Coverage

- 1- 11-13 m<sup>2</sup> per litre on smooth surfaces at 70-90 µm wet layer. On rough or absorbent surfaces, more paint may be required.



**EDWARD  
BULMER**  
NATURAL PAINT

# Water Based Gloss Woodwork and Metalwork

## **Cleaning**

Remove paint residue from tools with waste paper or a cloth and stand tools in warm, soapy water and then rinse. Stubborn residues might need **Natural Paint Soap**

## **Storage**

Store out of reach of children. Unopened containers of **Edward Bulmer Water Based Gloss** should be stored in frost-free place at 18°C and will last at least 24 months.

## **Composition**

Consistently ecological choice of raw materials (see full declaration on website).

Ingredients: Water, Decovery®, mineral pigments, silicic acid, cellulose, surfactants made of rapeseed oil and castor oil, silicates, Preservatives: liquid ammonia, benzyliothiazolinone preservative sodium pyrithione.

## **Maintenance and follow-up treatment**

Clean painted surfaces gently with mild soapy water only and without aggressive abrasives or abrasive sponges, do not use any caustic solutions. Weathered or damaged paint should be cleaned and lightly sanded and repainted with 1-2 coats of fresh paint. Where bare wood is exposed follow the guidelines set out above.

## **Health and Safety**

EC Safety Data Sheet available on request.

Observe the customary protective measures, e.g. ensure adequate skin protection and ventilation during application.

## **Disposal**

Please empty and recycle all tins. Dried residues may be disposed of a household waste. Liquid residues are subject to waste code (EWC code): 080120 Designation: Paints, Lacquers

Please call our dedicated Customer Service team on 01544 388 535 with any queries or email us at [info@edwardbulmerpaint.co.uk](mailto:info@edwardbulmerpaint.co.uk)

NB: It is our objective to provide, through this technical information, advice based on our skills and practical experience. Any instructions given are non-binding and do not release the user from his or her liability to check for product suitability and application methods him/herself with regard to the surface used. Technical modifications may result from product development. Upon publication of a revised or new version, these instructions will automatically lose their validity. We mix all our paint colours and use batch codes to help us track our stock. Whilst every effort is made to ensure colour consistency between batches, different batches should be mixed together before use. It is the responsibility of the end user to test a small area with full preparation before embarking on the whole project. The details contained in the EU Safety Data Sheets in their current form dictate liability for classification in terms of the Hazardous Substances Regulations. The Terms and Conditions of Sale which this purchase bind you to are available on our website, or on request from Head Office, please read them before using our products. If we are not notified that they are unacceptable we shall take the use of our products as tacit agreement to them. Products remain the property of Natural Paints UK until fully paid for.

Head Office: Court of Noke, Pembridge, Herefordshire, HR6 9HW [www.edwardbulmerpaint.co.uk](http://www.edwardbulmerpaint.co.uk)