



**EDWARD
BULMER**
NATURAL PAINT

Plaster Primer Preparatory Product

All new plaster must be primed. As there is no plastic in our Emulsion it will quickly be absorbed into surfaces, like new plaster, if primer has not been used. We recommend our natural Plaster Primer which is a water-based product for absorbent or irregularly absorbent wall and ceiling surfaces. Our Plaster Primer is breathable and perfect for use on lime plaster and gypsum plaster and is made exclusively from natural raw materials. It provides optimum absorbency for the subsequent application of Edward Bulmer Natural Paint.

Pack Size

2 litre and 5 litres.

Description

An economical, easy to apply, solvent-free, water-based primer with virtually no smell. Breathable (vapour permeable – Sd <0.1) and non-film forming. Milky appearance in tub and dries transparent.

Surface Preparation

Make sure that the plaster surface is clean, dry, firm and free from dust and oil. Any sinterskin should be matted with sandpaper before application.

Fill all holes, cracks and imperfections with a suitable filler before any primer or paint products are applied. All buttered joints must be filled. Choice of filler should be based on compatibility with the surface to be filled, we recommend our Natural Wall Filler. All sanding should be completed and all dust removed, before starting painting.

Application

Dilute the product 1:1 with clean water and then stir thoroughly. Apply one to two coats of the primer (depending on absorbency of the surface) by brush or spray equipment. Apply liberally to the surface. Allow to dry fully before application of any further paint products.

Observe information supplied by manufacturers of plasterboard.

We do not recommend priming with acrylic primers or using a mist coat of acrylic paint as this will reduce the breathability of the top coat.

Drying (20 °C, 60 % relative humidity)

Dry and re-coatable after 4 to 6 hours. Significant drying delays are caused by high humidity, low temperatures and high application volumes.

Coverage

Approximately 20 m² per litre per coat (after dilution). Coverage depends on the quality and absorbency of surface and the method of application.

Cleaning

Brushes and other tools can be cleaned immediately after use with water, add detergent if necessary.

Disposal

Do not empty residues into drains. For Liquid residues: Waste code 080120 applies. Emptied containers with dried Product residues can be returned for recycling.

Storage

Store out of reach of children. Unopened containers of this Plaster Primer can be stored in a cool, frost-free place at 18°C will last at least 12 months.

Physical / Technical Features

Working conditions: Min. 10°C, max. 30°C Max. Relative humidity 70%.

Avoid direct sunlight.

Density: 1.0 g/cm³

Sd value (H₂O) <0.1m

VOC content: EU Limit (Cat A/a): 30 g/L. **This product < 0.1 g/l.**

Health and Safety

The composition of this Plaster Primer is considered non harmful to the health, however the usual protection measures should be observed. Use skin protection and adequate ventilation. In case of skin contact, rinse off immediately with water. In case of eye contact, flush immediately with plenty of water and consult a physician. See the Safety Data Sheet for more information.



EDWARD
BULMER
NATURAL PAINT

Plaster Primer Preparatory Product

Please call our dedicated Customer Service team on 01544 388 535 with any queries or email us at info@edwardbulmerpaint.co.uk

N.B. The information on this data sheet is correct to the best of our knowledge and experience. EBNP reserves the right to modify data contained herein, without notice. The information supplied does not absolve users from responsibility to carry out their own tests and experiments, nor does it imply any legally binding assurance of certain properties or suitability for any specific purpose. Conditions of service and application may be beyond our control, so no liability whatsoever can be accepted based on the information supplied here.

Head Office: Court of Noke, Pembridge, Herefordshire, HR6 9HW www.edwardbulmerpaint.co.uk