

Fine Grip Coat Primer

PRIMER PRODUCT OVERVIEW

Product description

A specialist water-based primer for difficult plaster and mixed masonry surfaces. Made from fully declared natural ingredients, it provides excellent adhesion and creates the ideal base for Edward Bulmer Natural Emulsion. Suitable for lime plaster and other breathable substrates.

Product benefits

- Excellent adhesion to difficult surfaces
- Fully declared natural ingredients
- Plastic free, including no microplastics
- Preservative & MIT-free
- Solvent free
- Water-based
- Creates an ideal base for Natural Emulsion
- Fine textured finish
- Low VOC (<1g/L)

Ingredients

Cellulose, mineral fillers, potassium silicate, Replebin, silicate, surfactants made of rapeseed and castor oils, titanium dioxide, water

Suitable for

- ✓ Interior walls & ceilings
- ✓ Gypsum plaster
- ✓ Lime plaster
- ✓ Plaster board
- ✓ Concrete
- ✓ Stone
- ✓ Brickwork
- ✓ Clay
- ✓ Previously painted surfaces
- ✓ Wallpaper
- ✓ Old coatings capable of wetting (dispersions, lime paints, silicate and casein paints)
- ✗ Interior woodwork
- ✗ Radiators

We recommend our Water-Based Wood Primer for interior and exterior woodwork.

Coverage

Average coverage up to 12m² per litre*

2.5L = **30m²**
5L = **60m²**

*Coverage varies depending on substrate absorbency.

Drying time



Surface dry and recoatable **after 4-6 hours**



Fully dry and loadable **after 48 hours**

These times are calculated on 20°C room temperature and 65% relative humidity. High humidity levels and low temperatures are likely to prolong drying times.

Product Specifics

Finish: Fine textured (<0.05mm)

VOC Content: <1g per litre
(EU limit for Cat A/a: 30g per litre)

Breathability: <0.09m (SD value) Highly Breathable

Density: 1.38g/ml

Coverage: 12m² per litre

Binder: Replebin® 100% biogenic plant-based binder

Temperature: Optimal: 20-23°C / Min: 10°C / Max: 35°C

Available sizes



Fine Grip Coat Primer

PRIMER PREPARATION & APPLICATION

Surface Preparation

Suitable substrates:

Gypsum plaster, plasterboard, lime plaster, concrete, brickwork, clay, wallpaper and previously painted surfaces capable of wetting.

General substrate requirements:

The substrate must be clean, dry, grease-free and sound. Remove incompatible coatings, including soft distempers, completely before application.

For walls affected by staining, test compatibility first. If staining persists, apply a suitable stain-blocking primer.

Previously painted & wallpapered surfaces:

Wash previously painted surfaces thoroughly. Lightly sand glossy surfaces, including sinter skin, and test for compatibility. Reseal wallpaper seams and remove any paste residues.

Fill all holes, cracks and imperfections using a compatible filler; we recommend our Natural Wall Filler. Complete all sanding and remove dust before priming.

Application

Stir thoroughly before and during use, as the product will naturally settle. Apply 1–2 coats by brush or roller. If required, dilute with up to 5% water.

Recoat only when the previous coat is fully dry. There is no need to sand between coats.

We do not recommend using acrylic primers or acrylic mist coats, as these reduce the breathability of the finished system.

Visit edwardbulmerpaint.co.uk for more detailed application guidance.

Brush:

Use a high-quality natural bristle or synthetic brush. Maintain a wet edge throughout application.

Roller:

Apply using a medium-pile roller, maintaining a wet edge for an even finish.

Fine Grip Coat Primer

PRIMER **CLEANING & CARE**

Cleaning

Wipe excess product from brushes, rollers and other tools immediately after use. Wash thoroughly with warm, soapy water.

Storage

Store in an airtight container in a cool, dry, frost-free environment. Unopened containers stored at 18°C have a shelf life of 12 months from the date of production.

Maintenance & Topcoating

Once fully dry, apply our Natural Emulsion. The fine texture of the primer will disappear beneath the finish coats. If topcoats are delayed for a significant period, an additional coat of Fine Grip Coat Primer may be required.

Paint Container & Packaging Disposal

All components of the packaging are recyclable. Leave leftover paint to dry in the container before disposing of it as household waste. Do not wash liquid paint into drains – dispose of responsibly under EWC Code 080120. Recycle empty tins through your local household recycling scheme where available.

Health & Safety

The composition of this product is not considered harmful to health; however, the following precautions should be taken: Ensure adequate ventilation and skin protection when handling and using the paint. In case of skin contact, rinse thoroughly with plenty of water. In case of eye contact, rinse thoroughly and seek medical advice. Wear appropriate personal protective equipment when spraying and do not inhale spray mist. The Safety Data Sheet for this product is available at edwardbulmerpaint.co.uk. Dispose of paint and packaging in accordance with the legal regulations. Keep out of reach of children.

PRIMER **SUPPORT & ADVICE**

For further information,
please contact us.

By phone: +44 (0)1544 388 535

By email: info@edwardbulmerpaint.co.uk

By post: Edward Bulmer Natural Paint, Court of Noke, Pembridge, HR6 9HW

edwardbulmerpaint.co.uk

Disclaimer

The information on this Technical Data Sheet is correct to the best of our knowledge at the time of publishing. Natural Paint UK Ltd reserves the right to amend specifications without notice. Users must ensure the product's suitability for their intended application. Conditions of service and application are beyond our control; no liability whatsoever can be accepted based on the information supplied here.
