Natural Wall Filler

FILLER **PRODUCT OVERVIEW**

Product description

A natural, self-mix powder filler for repairing cracks, holes and uneven surfaces on interior plaster, brick and stone. Free from acrylic and PVC, it creates a smooth, breathable surface ready for decorating with Edward Bulmer Natural Paint.

Product benefits

- Free from acrylic & PVC
- Breathable
- Easy to sand
- Suitable for plaster, brick & stone
- Ideal for filling cracks, holes & joints
- Creates a smooth surface before painting
- Compatible with Edward Bulmer Natural Paint

Ingredients

Citrate, mineral Fillers, natural gypsum, titanium dioxide, xanthane

Suitable for

✓ Interior plaster
✓ Brick
✓ Stone
✓ Cracks
✓ Holes
✓ Joints

✕ Exterior use
✕ Floors
✕ Areas of constant moisture

Available sizes



Coverage

Coverage varies depending on the depth of repair.

Approx. **0.8–1.0kg powder per m².**

Drying time

Pot life: Approximately **40 minutes**

Fully hardened: Approximately **36 hours**

These times are calculated on 23°C room temperature and 50% relative humidity.

Product Specifics

Finish: Smooth

Density: Approx. 1.5g/cm³

Minimum application temperature: 10°C

Natural Wall Filler

FILLER **PREPARATION & APPLICATION**

Surface Preparation

Suitable substrates:
Interior plaster, brick and stone.

General substrate requirements:
The substrate must be clean, dry, sound and free from grease and loose material. Brush or vacuum away dust and debris before application.

Ensure plastered surfaces are alkali-free before filling.

Lightly dampen the surface before application. Do not prime with Natural Plaster Primer before applying the filler.

Application

Do not mix more filler than can be used within the pot life.

Mix:

- 2 parts filler : 1 part water (by weight)

or

- 3 parts filler : 1 part water (by volume)

Mix thoroughly to form a smooth, lump-free paste. Allow to stand for 2 minutes, then remix, adding a little more water if required.

Apply evenly using a filling knife, spatula or smoothing trowel.

Allow to harden fully before sanding if required.

Filling wall tile joints:
When filling wall tile joints, dampen the joints first. Apply the filler in two passes, then clean with a damp sponge once a white film appears. Lightly dampen the joints again after approximately five hours to aid curing.

Before Decorating

Allow the filler to harden completely before sanding if required.

Once fully cured, apply the appropriate Edward Bulmer primer before decorating with Edward Bulmer Natural Paint.

Natural Wall Filler

FILLER **CLEANING & CARE**

Cleaning

Clean tools immediately after use with cold water.

Storage

Store in the original sealed container in a cool, dry, frost-free environment. Unopened containers stored at 18°C have a shelf life of 12 months from the date of production.

Paint Container & Packaging Disposal

All components of the packaging are recyclable. Leave any unused mixed filler to harden before disposing of it as household waste. Do not wash liquid residues into drains. Dispose of liquid waste responsibly under EWC Code 080120.

Health & Safety

The composition of this product is not considered harmful to health; however, the following precautions should be taken: Ensure adequate ventilation and skin protection when handling and using the paint. In case of skin contact, rinse thoroughly with plenty of water. In case of eye contact, rinse thoroughly and seek medical advice. Wear appropriate personal protective equipment when spraying and do not inhale spray mist. The Safety Data Sheet for this product is available at edwardbulmerpaint.co.uk. Dispose of paint and packaging in accordance with the legal regulations. Keep out of reach of children.

FILLER **SUPPORT & ADVICE**

For further information, please contact us.

By phone: +44 (0)1544 388 535
By email: info@edwardbulmerpaint.co.uk
By post: Edward Bulmer Natural Paint, Court of Noke, Pembridge, HR6 9HW

edwardbulmerpaint.co.uk

Disclaimer

The information on this Technical Data Sheet is correct to the best of our knowledge at the time of publishing. Natural Paint UK Ltd reserves the right to amend specifications without notice. Users must ensure the product's suitability for their intended application. Conditions of service and application are beyond our control; no liability whatsoever can be accepted based on the information supplied here.